

Part Number	
Project Notes	

High-Bay HB SERIES

Product Description:

The DLC approved HB Series High-Bay provides lumen packages from 18,000 to 37,000 lumens with illumination performance that will allow a one for one replacement of 250W, 400W, 750W HID and multi-lamp fluorescent high-bay fixtures. With extremely long rated lifetimes, zero restrike time, and light-weight die-cast construction, the HB Series is a direct replacement for HID and fluorescent light sources and provides the added benefits of energy savings and reduced relamp maintenance costs.

Performance Summary:

Delivered Light Output: up to 37,000 lumens
Input Power: up to 240W on HB1, 330W on HB3 Electronic driver
Power Source: Electronic driver
CRI: 84
CCT: 5000°K
Input Voltage: 120-277 VAC
Beam Spread: 95°
Limited Warranty: 10 Year LED Driver / 5 Year LED Lamp
Mounting: Hook, 18/3 5' SJO cord with connector
Weight: 10 lbs
Dimming: 0-10v Standard
Listing: cUL Listed, DLC Approved, LDL Approved
LED Lifespan L70: 60,000 hours



Ordering Information

Example: **HB1-54-24U-850-12-H-A-D**

PRODUCT	TYPE OF CONSTRUCTION	LUMEN PACKAGE	CRI	KELVIN	INPUT VOLTAGE	MOUNTING	OPTIC	CONTROLS
HB1	54 – IP54	Refer to Table Below	8 – 83+	Available in: 4000°K 5000°K	12 – 120-277	H – Hook, cord	A – Acrylic	D – 0-10V
HB3	54 – IP54	37D						

	LUMEN PACKAGE	UPLIGHT	DOWNLIGHT	FIXTURE WATTS	LUMENS/WATT	CERTIFICATIONS	
						DLC	LDL
HB1	20U - 20,000 Lumens	<input checked="" type="checkbox"/>		220	101	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	22D - 22,000 Lumens		<input checked="" type="checkbox"/>	212	100	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	24U - 24,000 Lumens	<input checked="" type="checkbox"/>		225	112	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
	27D - 27,000 Lumens		<input checked="" type="checkbox"/>	250	106	<input checked="" type="checkbox"/>	
HB3	37D - 37,000 Lumens		<input checked="" type="checkbox"/>	325	113		<input checked="" type="checkbox"/>

Product Dimensions

